





TYPICAL APPLICATIONS



Natural convection currents generated by circulation heater thoroughly heat tank contents



Circulation heaters can be series piped for higher outputs

DESIGN SPECIFICATIONS

PRESSURE RATING:

Standard	150
	300
	600
	900

TEMPERATURE CONTROL:

Standard	NONE
	0-100°F
	60-250°F
	150-355°F
	300-700°F

FLANGE OR SCREWPLUG SIZE:

1"	1-1/4"
2"	2-1/2"
3"	4"
5"	6"
8"	10"
12"	14"
16"	18"
20"	22"
24"	SPECIAL

FLANGE OR SCREWPLUG MATERIAL:

Standard	Steel
	304 SS
	316 SS
	Brass
	Incoloy

BODY STYLE

Flanged-circulation
Screwplug-circulation

KILOWATTS:

PLEASE SPECIFY

VOLTAGE:

120	208
240	480
600	SPECIAL

PHASE:

1	3
---	---

OVERALL LENGTH (Inches)

PLEASE SPECIFY

WATT DENSITY

PLEASE SPECIFY

ELEMENT SHEATH MATERIAL

Steel
Copper
Incoloy
Inconel
Stainless Steel

HOUSING:

NEMA 1
NEMA 4
NEMA 7
NEMA 12

OPTIONS:

PLEASE SPECIFY

WEST HEAT INDUSTRIES LTD

1680 Church Avenue
Winnipeg, Manitoba R2X 2W9
www.westheat.com

ELECTRICAL HEATING DIVISION

Phone: (204) 694-2129
Fax: (204) 694-2098
Fax Orders To: 1-800 358-7711