



RADIANT & PUMP HOUSE HEATERS

UTILITY & PUMP HOUSE HEATER:



Model	Volts	Watts	H	Dimensions			Weight
				W	D		
U1225	120	250	5"	17"	4"	6	
U1250	120	500	5"	17"	4"	6	
U1275	120	750	5"	17"	4"	6	
U12100	120	1000	5"	17"	4"	6	
U2425	240	250	5"	17"	4"	6	
U2450	240	500	5"	17"	4"	6	
U2475	240	750	5"	17"	4"	6	
U24100	240	1000	5"	17"	4"	6	

All heaters contain built-in thermostats.
This heater may be mounted vertical or horizontal on a wall surface.
Optional stainless steel

RW SERIES BATHROOM HEATER

Model	Surface or		Volts	Watts	H	Wall Opening Dimensions			Recess	Surface
	Recess					W	D			
RW1225	S or R		120	250	15-1/2"	11-1/8"	2"	7	8	
RW1250	S or R		120	500	15-1/2"	11-1/8"	2"	7	8	
RW1275	S or R		120	750	15-1/2"	11-1/8"	2"	7	8	
RW12100	S or R		120	1000	15-1/2"	11-1/8"	2"	7	8	
RW2425	S or R		240	250	15-1/2"	11-1/8"	2"	7	8	
RW2450	S or R		240	500	15-1/2"	11-1/8"	2"	7	8	
RW2475	S or R		240	750	15-1/2"	11-1/8"	2"	7	8	
RW24100	S or R		240	1000	15-1/2"	11-1/8"	2"	7	8	

Grill is chrome-plated steel and aluminum frame.
All heaters have built-in thermostats.

Workers Stay Comfortable, Perform More Efficiently

SALAMANDER HEATERS

FAN FORCED, CLEAN, ODOR-FREE INSTANT ELECTRIC HEAT

The portable electric Salamander provides fan-forced, clean, odor-free and instant electric heat. The heater enclosure, which can be pivoted, is mounted on a two-wheeled cart, which allows for directed warm airflow to any desired location. The unit is constructed of non-corrosive materials and the heater enclosure is painted safety yellow to maximize visibility and safety.



UL 15 KW & 30 KW Models SP 15 KW & 30 KW Models (240V & 480V) ETL

MODEL	ITEM NO.	KW/BTU	TEMP RISE	VOLTS/PHASE	AMP	HZ	CABLE KIT NO.	UL	ETL	CSA
FES-1520-3	8814410	15/51195	45° F	208/3	42	60	(3 Phase) 8805000	×		
FES-1524-3D	8814010	15/51195	45° F	*240/3 or 1	36/63	50/60	(3 Phase) 8805100	×	×	×
FES-1548-3D	8814110	15/51195	45° F	*480/3 or 1	18/32	60	(3 Phase) 8804800	×	×	×
FES-1560-3	8814510	15/51195	45° F	600/3	15	60	(3 Phase) 8804800	×		×
FES-1024-1C	2001310	10/34130	30° F	240/1	42	50/60	Standard			
FES-3048-3	8814310	30/102,390	90° F	480/3	36	60	(3 Phase) 8805000	×		×
FES-3060-3	8814610	30/102,390	90° F	600/3	30	60	(3 Phase) 8805100	×		×

*Conversion to single-phase will VOID UL, ETL Listing and CSA Certification Cable Kits are 25', SO type, plug not included. See page 25 for Cable Kits.
"WARNING: Do not use any product without first reading the safety and installation instructions packed with each product."

WEST HEAT INDUSTRIES LTD

1680 Church Avenue
Winnipeg, Manitoba R2X 2W9
www.westheat.com

ELECTRICAL HEATING DIVISION

Phone: (204) 694-2129
Fax: (204) 694-2098
Fax Orders To: 1-800 358-7711