





## KT - KICK SPACE HEATER



**Motor:** Thermally protected, and permanently lubricated.  
**Fan:** Tangential (Squirrel cage) blower provides whisper quiet operation. 85 CFM.  
**Element:** Dual wattage element allows for field adjustment. Made from Ni-Chrome alloy open coil wire wrapped around a mica insulator.  
**Thermal Cutout:** Safety limit turns off power to the element if it overheats and automatically resets.  
**Safety Light:** Illuminates when the thermal limit control trips.  
**Wall Box:** 20 gauge electro-galvanized steel.  
**Grill:** 20 gauge cover finished in a gloss white powder coated paint.  
**Options:** 1-Pole or 2-Pole unit mount thermostat, retrofit grill, and overlap grill.



### SELECTION CHART

Heaters shipped complete with wall can & grill


MODEL	UPC VENDOR #783940	VOLT	WATTAGE *	Wt
KT1210	12256	120	1000 or 500	8
KT1212	12259		1200 or 600	
KT1215	12262		1500 or 750	
KT2410	12271	240 208	1000 or 500 750 or 375	
KT2412	12272	240 208	1200 or 600 900 or 450	
KT2415	12277	240 208	1500 or 750 1125 or 562	

\* Factory wired for full wattage, field convertible to half watt.

### Accessories


MODEL	UPC VENDOR #783940	Description	Wt
KT-1	12298	Single Pole Unit Mount Thermostat Kit	1
KT-2	12301	Double Pole Unit Mount Thermostat Kit	
A-Alternate	12275	Wall Trim Grill - overlaps 1/2" on all sides	
B-Retrofit	12276	Converts older 24" grills to 14 1/2" heater	

## KVC - COVE HEATER




Height- 4" Depth- 3"


The faceplate performs a two-fold function: (1) it focuses the infrared rays and (2) directs the heat downward along cold perimeters and toward the center of the room. The surface design increases the radiating surface, thereby increasing the comfort level of the room faster and insuring more rapid recovery from heat losses.



**Radiation:**  
A large portion of the heat produced is emitted as radiant infrared invisible rays.



**Convection:**  
A portion of the heat produced is transmitted by natural convection from the top of the heater



**Re-Radiation:**  
The air heated by convection travels horizontally across the ceiling. And it also becomes a source of radiant heat and re-radiates heat through out the entire room.

### SELECTION CHART

MODEL	UPC Vendor #783940	WATTS	LENGTH	Wt.	VOLTS
KCV1202	11801	225	24"	3	120
KCV1204	11800	450	34"	5	
KCV1206	11803	600	47"	7	
KCV1207	11806	750	59"	8	
KCV1210	11812	1000	83"	11	208
KCV2404	11824	350	34"	3	
KCV2406	11827	450	47"	7	
KCV2407	11830	560	59"	8	
KCV2409	11833	675	71"	9	240
KCV2410	11836	750	83"	11	
KCV2412	11839	900	94"	13	
KCV2415	11842	1125	118"	15	
KCV2404	11824	450	34"	3	240
KCV2406	11827	600	47"	7	
KCV2407	11830	750	59"	8	
KCV2409	11833	900	71"	9	
KCV2410	11836	1000	83"	11	240
KCV2412	11839	1200	94"	13	
KCV2415	11842	1500	118"	15	

### ACCESSORIES

MODEL	UPC Vendor #783940	Description
KCVT-1	11845	Single Pole Unit Mount Thermostat Kit
KCVT-2	11848	Double Pole Unit Mount Thermostat Kit
Blank Sections		Custom Blank Sections for fill in are made to order - Non Cancellable Non Returnable

## WEST HEAT INDUSTRIES LTD

1680 Church Avenue  
Winnipeg, Manitoba R2X 2W9  
[www.westheat.com](http://www.westheat.com)

ELECTRICAL HEATING DIVISION

Phone: (204) 694-2129  
Fax: (204) 694-2098  
Fax Orders To: 1-800 358-7711