

Digital Multimeter with Type K Temperature Probe



- ❑ 3- ½ Digit, 1.2% basic accuracy
- ❑ 8 Functions, 23 Ranges
- ❑ DCV, ACV, and OHMS measurement
- ❑ Capacitance 20uF~20mF
- ❑ Frequency measurement 10Hz to 40kHz
- ❑ Type K Temperature measurement
-20°C~-750°C, -4°F ~1400°F
- ❑ Phase Indicator
- ❑ Diode/Continuity test

H-TMDR-DMM0-0124-A000

DC Voltage Ranges:	200mV, 2V, 20V, 600V, ± (1.2% +1dgt)
AC Voltage Ranges:	200mV, 2V, 600V. ± (2.0% +4dgts)
Resistance Ranges:	200Ω, 2kΩ, 20KΩ, 200kΩ, 2000KΩ, 20MΩ, 2000MΩ, ±(1.0~2.0 % +4dgts) 200Ω, ~10MΩ
Capacitance Ranges:	20uF, 200uF, 2000uF, 20mF
Temperature:	-20°C~750°C, -4°F~, 1400°F, ± (3.0%rdg +2°C), ± (3.0%rdg+4°F)
Frequency Range:	Auto ranging 10Hz to 40kHz. ± (0.1%+2dgts)
Phase Indicator:	Freq. 45Hz to 450Hz, Voltage: 80V to 480V
Overload Protection:	Temperature: 60VDC or 24V AC RMS
	Capacitance: 250V/1.5A 500V DC for other ranges
Diode Test, Continuity Beeper <100Ω	
General	
Power Requirement:	One 9V battery
Dimensions:	5.8"x2.8"x1.5" (147x70x39mm)
Weight:	12 oz (340g)
Accessories:	Test leads, holster, battery, K-type, thermocouple, and owner's manual

DIGITAL THERMOMETER



SINGLE INPUT DIGITAL THERMOMETER

- Temperature range -50°C to 1300°C / -58°F to 2000°F
- Front panel offset calibration
- Maximum/minimum settings
- Accuracy ± 0.3% rdg + 1°C (2°F)
- Accepts standard miniature thermocouple plug
- Resolution switchable 0.1° / 1.0°
- Low battery indicator
- Data hold function
- Probe disconnect warning light

INCLUDES THE FOLLOWING ACCESSORIES:

- K type immersion probe ¼" / 10 cm for temp -50°C to 200°C / -58°F to 392°F
- 4' / 1.2m wire K type thermocouple - 50°C to 200°C / -58°F to 392°F
- Protective rubber holster
- 9 volt battery

H-TMDR-DTM0-305B-P000

WEST HEAT INDUSTRIES LTD