



# ACCESSORIES

## TERMINAL COVERS: HIGH TEMPERATURE

(For use with post terminals)

Individual Ceramic Terminal Covers are designed to protect the operator from exposed terminals. The cover body is slotted to receive two wires and may be installed after wiring has been completed.



## CERAMIC WIRE NUTS


Size	Part #
10-12	H-ACCN-NWC8-1012-AWG0
14, 16, 18	H-ACCN-NWC8-1418-AQG0

POST SIZE	PART #
10-24 threads	H-ACIN-TCCC-1024-0000
10-32 threads	H-ACIN-TCCC-1032-0000

## CERAMIC WIRE BUSHING

Helps to prevent wire abrasion in high temperature applications

H-ACCS-CBWN-20CB-0000



## SILICONE HOOD

Use to protect terminals from damage and to minimize shock hazard

Heat resistant up to 400°F

Available in 0.260", 0.290"/0.315" & 0.430" Diameter

Sold in bags of 50



- .260": H-ACIN-SH00-0260-0000
- .290"/.315": H-ACIN-SH00-0290-0000
- .430": H-ACIN-SH00-0430-0000



## NON-FRAYING FIBERGLASS SLEEVING

Braided glass, heat-treated to remove textile sizing and provide fray resistance when cut. Flame retardant.



SLEEVING SIZE	PART NO.
#0, Natural	H-WISL-AC10-G001-0000
1/4", Natural	H-WISL-AC10-G001-0025
#3, Natural	H-WISL-AC10-G001-0300
#5, Natural	H-WISL-AC10-G001-0500

Acrylic resin-coated fiberglass sleeving. Highly flexible, resists mechanical damage. Compatible with most wire enamels and varnishes. Excellent thermal endurance.

SLEEVING SIZE	PART NO.
1/2"	H-ACDR-AG00-0100-0000



## CONDUIT

High temperature, stainless steel, flexible type (for abrasion and flexing protection)

part #	I.D.	O.D.
H-ACIN-CSS0-C250-0000	5/32"	1/4"
H-ACIN-CSS0-C375-0000	9/32"	3/8"
H-ACIN-CSS0-C500-0000	3/8"	1/2"

Fax Orders To: 1-800 358-7711

1680 Church Avenue - Winnipeg, Manitoba - R2X 2W9 - Phone: (204) 694-2129 - Fax: (204) 694-2098 - www.westheat.com