

ACCESSORIES



STAINLESS STEEL REDUCING BUSHING


3/8 NPT to 1/8 NPT
Used in Thermowells to reduce for compression fittings

H-TCAD-1NP8-0003-8SRB

1/8 COMPRESSION FITTINGS

Used to seal 3/16 diameter thermocouples.
Available in Stainless Steel and Brass

H-TCCF-A0T1-8003-16B0 – Brass
H-TCCF-A0T1-8003-16SS – Stainless




MALE ALUMINUM CUPS

H-ACCN-C2P0-UT90-0000

THERMOWELLS

6" – H-TCAC-TWSS-N050-0600
12" – H-TCAC-TWSS-N050-1200

Welded tube wells are also available in 24" and 36" lengths and in steel, or stainless steel. Outside threads are 1/2" NPT for connection to your system and 3/8" NPT inside to accept a compression fitting. Special non-welded bar stock wells are also available for custom application in a variety of materials.



HEATER INLET WITH BOX

Porcelain terminal base, metal shell and screw terminals.

H-ACCN-MSR0-1111-0430



EUROPEAN CONNECTORS

| Style | # of Prongs | Part # |
|----------|-------------|-----------------------|
| Straight | 2 | H-ACCN-PE2S-1111-0340 |
| 90° | 2 | H-ACCN-PE29-1111-0345 |
| Straight | 3 | H-ACCN-PE3S-1111-0455 |
| 90° | 3 | H-ACCN-PE39-1111-0455 |

WEST HEAT INDUSTRIES LTD