

GAC / Mineral Stone Filters



This filter is used to polish water after being treated by a commercial R/O. The granular activated carbon (GAC) reduces any residual taste and odor that may be present in the tank and the mineral stones add healthy minerals such as calcium, magnesium, potassium and sodium back into the water.

Manual Head	
Max Flow Rate	10 GPM
Mineral Tank Height	35"
Mineral Tank Diameter	8"
Media Volume	50 Lbs
WSFCA-1450-MSGA	

Iron Filters



This filter removes iron from your water supply thus preventing staining of appliances and metallic tasting water. Available in 2 chemical based models and 1 chemical free model all equipped with the 5600SE electronic control. Other models available upon request.

Features

- Three models to choose from to fit the application
- 5600SE electronic control with LED display and user friendly programming (1 Cu. Ft. model only)
- Meter initiated regeneration, with day override
- Fully adjustable regeneration cycles
- Bypass included with 3/4" MNPT Connections (1 Cu. Ft. model only)
- Heavy Duty mineral tank
- Electrical: 24V/60 Hz (120V to 24V wall mount transformer included)
- Optional reverse osmosis shut off switch available

Standard Iron Filters

Part #	Media Cu. Ft. (litres)	Pipe Size Inches (mm)	Max. Bed Capacity (ppm)	Iron Removal Capacity (ppm)	Flow Rates GPM (LPM)			Mineral Tank Size Inches
					Service	Peak	Backwash	
WSF00-7622-0000	1.00 (28)	3/4 (19)	8000	6000	3.0 (11)	5.0 (19)	4.0 (15)	9 X 48
WSF00-7623-0000	1.50 (42)	3/4 (19)	12000	9000	5.0 (19)	8.0 (30)	5.0 (19)	10 X 54

Other models available upon request

Chemical Free Iron Filters

Part #	Media Cu. Ft. (litres)	Pipe Size Inches (mm)	Iron Removal Capacity (ppm)	Flow Rates GPM (LPM)			Mineral Tank Size Inches
				Service	Peak	Backwash	
WSF00-7625-0000	1.00 (28)	3/4 (19)	30000	2.5 (9.5)	4.5 (17)	4.0 (15)	9 X 48 (229 X 1219)

Other models available upon request