

Trojan UV Max

Don't take safe drinking water for granted

Install our TrojanUVMax™ disinfection system and you no longer have to be concerned about pathogenic microorganisms such as E. coli, Cryptosporidium, and Giardia. Using ultraviolet (UV) light, the TrojanUVMax™ renders microorganisms unable to reproduce, resulting in safe drinking water.

The TrojanUVMax™ incorporates the most advanced UV technology, ensuring that you get a robust, cost-effective, and efficient solution to your disinfection needs. Add its convenience and safety, and the TrojanUVMax™ truly represents the way of the future for residential water disinfection.



Model	C4 WTRUV-6506-9200	D4 W-TRUV-6506-9400	E4 W-TRUV-6506-8200
Flow Rate	7-16 GPM	7 – 16 GPM	8-28 GPM
Safety cap & special lamp plug	✓	✓	✓
Lamp operation indicator	✓	✓	✓
Power supply operation indicator	✓	✓	✓
Sensor operation indicator	✗	D4 Plus	E4 Plus
Sensor with diagnostic test	✗	D4 Plus	E4 Plus
Reference card	✓	✓	✓
Lamp timer display	✗	✓	✓
Lamp timer reset button	✗	✓	✓
Mute button	✗	✓	✓
Solenoid valve	✗	Optional	Optional
External control relay	✗	Optional	Optional
Chamber material	304 SST	304 SST	316 SST
Inlet/outlet	3/4" NPT	3/4" NPT	1" NPT
Chamber dimensions	20.5" x 4"	20.5" x 4"	30" x 4"
Power supply dimensions	8.5" x 6"	8.5" x 6"	8.5" x 6"
Bulb part#	W-TRLA-6028-0500	W-TRLA-6028-0500	W-TRLA-6028-0600

Trojan UV Max Pro

The Pro Series from Trojan UV products is certified by NSF International against the requirements of NSF Standard 55 Class A. With both 10 and 20 gpm models and a full 5 year warranty against manufacturer's defects on the power supply and all electrical components (and 10 years on the water chamber!), the Pro Series is sure to meet all your disinfection requirements.

Features

Colour-coded plug and play connections	UV intensity monitor with diagnostic test
CoolTouch fan	Dynamic flow restrictor
Communications ports (two, RJ45)	Optional COM center control package
Optional Solenoid valve	316L SST Chamber material
Rated service life of lamp 2 years	Audible alarm mute button
New lamp button	Lamp age indicator
Lamp operation indicator	Sensor reading indicator



Standard 55
Class A